

CITIZEN

The right place to start for industrial printing

Entry level industrial



Space-saving design concept

The Hi-Open™ case lifts up vertically meaning that the printer's footprint does not change as the cover is opened making it ideal for tight spaces.

Optional peeler

An optional peeler can be added to the CL-S700DTII giving the peel-and-present function without the height of the full liner rewinder case.

Easy configuration

The large graphic LCD gives a clear indication of printer status and easy printer configuration.

CL-S700DTII

Label, Industrial

Applications

- Courier
- Logistic / Transport
- Retail
- Warehousing
- Healthcare
- Ticketing



High performance with easy access

TOMORROW'S PRINTING TODAY

CITIZEN

Specifications

Model	CL-S700DTII
Printing Technology	Direct Thermal
Resolution	203 dpi
Print Speed (maximum)	7 inches per second (175mm/s)
Print Width (maximum)	4 inches (104 mm)
Media Width (min to max)	1 - 4.6 inches (25 - 118 mm)
Roll Size (max), Core Size	Outside diameter 8 inches (200 mm) Core size 1 inch (25mm) Plus Outside media slot
Media Thickness (min to max)	63.5 to 254 µm
Media Length (min to max)	0.25 to 99.99 inches (6.35 to 2539.74mm)
Media Sensor	Fixed front
Main Interface	Dual Interface Serial (RS-232C), USB (version 1.1)
Mechanism	Hi-Lift™ metal mechanism with wide opening head
Control panel	4 buttons, 4-line back-lit graphic LCD
Emulations (Languages)	Datamax® DMX, Cross-Emulation™ - autoswitch between Zebra® and Datamax® emulations, Zebra® ZPL2® , CBI™ BASIC Interpreter, Eltron® EPL2®
Drivers and software	Free-of-charge from website, including support for various platforms
Flash (Non-Volatile Memory)	16 MB total, 4MB available for user
Size (W x D x H) and Weight	255 x 490 x 265 mm, 12.5Kg

Warranty 2 years on printer, 6 months or 50 Kms printhead

Citizen Systems Europe GmbH, Elizabeth House, 56-60 London Road, Staines-Upon-Thames, TW18 4HF, United Kingdom

CL-S700DTII

Label, Industrial

Features & Benefits

- Paper load: Front access for all operations including media and ribbon changing
- Printing Speed: Fast print out - up to 7 inches per second (175 mm per second)
- Media support: Very large media capacity - holds rolls up to 8 inches (200 mm)
- Display: Backlight LCD control panel for easy configuration
- Hi-Open™ case for vertical opening, no increase in footprint and safe closing.
- ENERGY STAR® compliant
- Recyclable packaging
- Basic peeler

CITIZEN SYSTEMS EUROPE GMBH